



Note: All Studs 7/8" dia. unless otherwise noted  
 Rivets 5/8"

Note: All rivet heads inside of pan must be hammered flat on account of brick work.

BILL OF MATERIAL.

No.	Mark	Sheets	No.	Mark	Angle Irons.
2	A	Top Plate, Side 3/8" x 29 3/8" x 94"	2	M	4" x 4" x 1/2" x 84"
1	B	" " Front 3/8" x 21" x 106 3/8"	2	N	4" x 4" x 1/2" x 106 3/8"
1	C	" " Back 3/8" x 7 1/2" x 106 3/8"	2	O	4" x 4" x 1/2" x 94"
2	D	Side 3/8" x 23 1/2" x 94"	2	P	2 1/2" x 2 1/2" x 3/8" x 67 1/2"
1	E	Bottom 3/8" x 26" x 94"	1	Q	2 1/2" x 2 1/2" x 3/8" x 102 1/2"
2	F	End 3/8" x 17 1/2" x 47 1/2"			Wrought Iron.
2	G	Cover " Front 3/8" x 16 1/2" x 24"	2	R	6" x 1" x 13"
2	H	" " Back 3/8" x 9 1/2" x 16 1/2"	2	S	6" x 1" x 16"
2	I	Corner " Front 3/8" x 11 1/2" x 25 1/2"	2	T	2" x 1 1/2" x 27"
2	J	" " Back 3/8" x 9 1/2" x 11 1/2"	1	U	2" x 3/4" x 8"
1	K	Air Trough 3/8" x 45" x 49"	2	V	2" x 3/4" x 10 1/2" Hinge
1	L	Damper 3/8" x 9" x 28"	1	Y	2 1/2" x 1 1/2" x 20" Front
2	X	Bolt Lock Plate 3" x 1 1/2" x 12"	1	Y	2 1/2" x 1 1/2" x 24" Back.

**FIRE PAN**  
 3800 CLASS ENGINES  
 L. A. & S. L. R. R.  
 LOS ANGELES CAL. APR. 9, 1917.  
 APPROVED:

*J. G. Harrison*  
 SUPT. MACHINERY.

